



STUMP GRINDER



Carbide teeth aggressively chews through any size stump with little wear. Our stump grinder's unique bi-directional cutting design creates a more aggressive cutting pattern, quickly chewing through the stump.



Adjustable skid shoe stabilizers provide support to minimize vibration.

FEATURES:

- Built for skid steers and loaders with the universal mount
- The Stump Grinder is the choice for arborists, large contractors, landscapers and maintenance departments for fast and efficient stump removal
- This unit features an offset cutting wheel for better visibility
- The Stump Grinder is easy to maneuver into tight spaces that are impossible to reach with other types of machinery without creating unnecessary damage to property
- Features a 24" diameter by 1/2" wide cutting wheel with 32 durable carbide teeth
- Cutting wheel turns at 1,100 rpm and can cut up to 8" below the ground
- High hub torque enables operator to cut full 55° swath 8" deep in less than 2 minutes.
- Electric over hydraulic drive system and has no gear box
- Adjustable anti-vibration skid shoes reduce vibration
- Bi-directional cutting design allows for dual pass operation without moving the skid steer and damaging the lawn
- Guard Assembly & Rubber Deflector helps to contain flying debris
- Heavy duty construction
- Durable charcoal paint finish

OPTIONS:

- Universal Wire Harness for hydraulic models with attachment controls. Fits CAT/ASV (8-Pin) CASE and John Deere / New Holland / Case / Bobcat (14pin) / Patch available for Bobcat 7 pin systems
- Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control systems



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

Box 59, Rockyford, Alberta Canada T0J 2R0
 Ph: (403) 947-2882 Fax: (403) 947-2892

F12

PRINTED IN CANADA



Drive System -
electric over hydraulic

Guard Assembly and Rubber Deflector prevents debris from flying needlessly.



24" diameter, 1/2" steel cutting wheel is fitted with carbide teeth for durability and speed.



Powered By:



Char-Lynn

Offset wheel allows operator better visibility. The stump grinder's hydraulic motor powers the 1/2" cutting wheel to an impressive 1100 rpm. The combination of a large 24" diameter cutting wheel and high hub torque cut a full 55 degrees swath 8" deep, in less than 2 minutes.



SPECIFICATIONS:

Part #	Model #	Cutting Wheel Dia.	Hydraulic Flow Req.	Max. Cutting Diameter	Maximum Cutting Depth	Cutting Arc	Cutting Wheel Speed	Teeth	Weight
900550	SG 24	24"	15 - 32 GPM	32"	8" Below Ground	55°	590 - 1,100 rpm	32	540 lbs

* The above numbers reflect the capacity of the attachment, and may be in access of the capacity of some skid steers. Please check your owners manual for specific capacities.



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

Box 59, Rockyford, Alberta Canada T0J 2R0
Ph: (403) 947-2882 Fax: (403) 947-2892

F13