



HYDRAULIC TELEBOOM



FEATURES:

- Built for skid steers and loaders with the universal mount
- The Hydraulic Teleboom is ideal for accurate and speedy handling of trusses, general construction materials, display sign, roofing/shingling materials, pole placement, building erection, anywhere that extra reach is required
- Tubular steel boom arm gives excellent strength and reduces overall attachment weight
- Can be adjusted from 112" to 256" from the comfort of your cab
- Holds materials securely with the use of its 3/4" x 7" pin main pin
- Angled Boom allows operator to transport loads with loader arms in a low position for added safety and load stability
- The hydraulic ram has a 72" stroke to maximize reach
- Durable charcoal grey paint finish



SPECIFICATIONS:

Part #	Model #	Width	Height	Length Fully Contracted	Length Fully Extended	Rated Load Fully Extended (Horizontal)	Rated Load Fully Contracted (Horizontal)	Skid Steer Min. Lift Req.	Weight
900770	HTB 1000	45.2"	18"	112"	256"	350 lbs.	700 lbs.	1750 lbs.	450 lbs.
	HTB 2000	45.2"	24"	102"	256"	1000 lbs.	3850 lbs.	2500 lbs.	705 lbs.

* The above numbers reflect the capacity of the attachment, not the skid steer. Please refer to your owners manual of your skid steer for lift capacities and hydraulic flow capabilities.



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

Box 59, Rockyford, Alberta Canada T0J 2R0
 Ph: (403) 947-2882 Fax: (403) 947-2892

E14