



MINI TILLER/LEVELER SOIL CONDITIONER



FEATURES:

- Ideal attachment for creating seedbeds and windrows
- Direct drive design
- Large solid urethane rubber tires
- Floating mount system
- On the go depth changes
- Optional power angling
- Adjustable side plates are removable
- Spiraled teeth for windrowing
- Durable black paint finish

AVAILABLE MOUNTS

- ASV/TEREX
- Bobcat (MT-52/55, 463/S70)
- Toro Dingo
- Vermeer
- Boxer
- Ditch Witch
- Ramrod
- Kanga
- Universal Skid Steer (Bobtatch)

Till, Level, and Condition Your Soil...

Why pay for manual labour when you can own this attachment that quickly pays for itself and earns dollars for your landscaping company? This attachment rakes stones and debris to either side or straight ahead for easy pick up. The aggressive teeth on the large diameter roller pulverize soil like an ordinary tiller with the benefit



of faster ground speed. The counter rotating rotor moves soil ahead of it as it tills, filling in low spots and chewing off high spots. It creates perfect seed beds and windrows. This attachment separates rocks, tears up sod and pulverizes dirt clods. It rakes and tills as deep as 2"



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

26 Spruce Park Drive, Strathmore, Alberta Canada T1P 1J2
Ph: (403) 901-1140 Fax: (877) 709-7027

PRINTED IN CANADA



MINI TILLER/LEVELER SOIL CONDITIONER

Floating mounting system follows the contour of the ground



Optional:
Toggle Control Harness is required if skid steer is **NOT** equipped with attachment control system. Only need when ordering hydraulic angling model.



Optional:
Universal wire harness for hydraulic models with attachment controls.

Direct drive motor gives higher production with lower maintenance

Large solid urethane rubber tires allow easier maneuverability over rough terrain



SPECIFICATIONS:

Angling	Manual (Hydraulic Optional)
Working Width	48"
Working Depth	0" - 2.5"
Maximum Angling	25°
Overall Width	56"
Overall Length	55"
Rated Flow	9-15 GPM
Operating Weight	470 lbs



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

26 Spruce Park Drive, Strathmore, Alberta Canada T1P 1J2
Ph: (403) 901-1140 Fax: (877) 709-7027

PRINTED IN CANADA