



V - BLADE



FEATURES:

- An excellent solution for high volume snow removal and fast efficient handling of dirt, gravel and sand (cannot handle aggregates)
- 6 position blade can windrow, push or plow
- Connects easily to skid steers, compact tractors and loaders with universal mount
- Heavy duty 3/16" plate gusseted mold board
- Spring trip feature dramatically decreases chances of blade damage
- 30 degree hydraulic angling places blade in an array of positions from full V for wind rowing to full inverted V for pushing material
- Blade is easily adjusted using an electric over hydraulic controller
- Adjustable skid shoes help protect cutting surfaces and blade from damage
- Blade is powered by two 2" hydraulic cylinders with one 18" rod
- 1/2" x 6" bolt on beveled carbon steel cutting edge is reversible for increased wear
- All pivot and ram points are serviceable
- Available in sizes from 84" to 108"
- Durable paint finish



Full V for wind rowing



Inverted V for pushing



Available for mini skid steer



Center rubber cleaner stops snow from going between blades

OPTIONS:

- 1" x 6" rubber cutting edges
- Blades extensions



SPECIFICATIONS:



Spring Trip helps prevent blade damage

Part #	Model #	Spring Trip	Blade Adjustment	Blade Width	Blade Width Full Angle	Blade Height	Approx. Weight
500998	VB 84	Yes	Hydraulic	86"	75"	28.25"	735 lbs.
500999	VB 96	Yes	Hydraulic	98"	85.5"	28.25"	775 lbs.
501000	VB 108	Yes	Hydraulic	110"	96"	28.25"	815 lbs.

* The above numbers reflect the weight of the implement. Please refer to your owners manual of your skid steer for lift capacities.



All products are subject to change without notice or liability.

Toll Free: 1-877-947-2882
www.conterraindustries.com

26 Spruce Park Drive, Strathmore, Alberta Canada T1P 1J2
 Ph: (403) 901-1140 Fax: (877) 709-7027

B3